



YEAR

2023

LINK LIN CHEUNG RD (from CHERRY ST to YAU MA TEI INT)

CORE STATION
ROAD NETWORK
ROAD TYPE3026
MAJOR
URBAN TRUNK ROAD

1. TRAFFIC FLOW VARIATION AND GROWTH



2. TRAFFIC CHARACTERISTICS (BY DIRECTION)

Parameter	All - Day	Mon. - Fri.	Sat.	Sun.
SOUTH BOUND				
A.A.D.T.	28800	30250	29520	23210
R 12 / 24 - %	73	74.6	70.5	66
R 16 / 24 - %	87.7	89.1	84.8	82.5
AM Peak Hour	0800-0900	0800-0900	0900-1000	0900-1000
One-way flow at AM peak hour	2430	2980	1880	1110
T - % (AM)	-	8.9	-	-
PM Peak Hour	1800-1900	1800-1900	1600-1700	1700-1800
One-way flow at PM peak hour	1780	1910	1810	1480
T - % (PM)	-	4.2	-	-
Prop.of commercial vehicles - 16 hr.	-	7.3	-	-
 A.A.D.T.	-	-	-	-
R 12 / 24 - %	-	-	-	-
R 16 / 24 - %	-	-	-	-
AM Peak Hour	-	-	-	-
One-way flow at AM peak hour	-	-	-	-
T - % (AM)	-	-	-	-
PM Peak Hour	-	-	-	-
One-way flow at PM peak hour	-	-	-	-
T - % (PM)	-	-	-	-
Prop.of commercial vehicles - 16 hr.	-	-	-	-

3. OTHER INFORMATION AND COMMENT

4. Vehicle classification and occupancy - Monday to Friday

Time		Class of vehicle									
		Motor Cycle	Private Car	Taxi	Private LB	PLB	Goods veh.		Non Fr. Bus	Fr. Bus	
							Light	M & H		SD	DD
0700-0800	Pro	1.8	35.4	27.7	5.8	0.3	14.7	7.9	4.3	0.0	2.0
	Ocp	1.1	1.4	2.2	7.9	18.5	1.3	1.2	13.2	0.0	30.7
0800-0900 Peak hour	Pro	2.4	51.0	22.2	1.3	0.6	13.6	3.7	3.2	0.0	2.0
	Ocp	1.1	1.4	2.2	4.3	16.7	1.6	1.4	14.2	0.0	58.5
0900-1000	Pro	2.1	50.2	25.5	0.0	0.0	17.5	3.6	0.4	0.0	0.8
	Ocp	1.1	1.4	2.1	0.0	0.0	1.7	1.1	6.3	0.0	39.5
1000-1100	Pro	2.3	44.8	24.4	0.8	0.0	20.9	4.6	1.4	0.0	0.8
	Ocp	1.1	1.4	2.2	1.3	0.0	1.5	1.3	2.2	0.0	23.2
1100-1200	Pro	3.8	47.4	26.1	0.7	0.2	15.7	3.7	1.6	0.0	0.9
	Ocp	1.0	1.4	2.2	2.0	7.0	1.4	1.3	3.0	0.0	17.6
1200-1300	Pro	2.1	48.2	27.6	0.8	0.2	12.6	5.4	2.1	0.1	0.9
	Ocp	1.2	1.5	2.1	4.3	14.0	1.5	1.3	11.2	1.0	21.4
1300-1400	Pro	1.7	42.9	27.3	0.6	0.0	16.8	7.7	2.1	0.0	0.9
	Ocp	1.0	1.4	2.2	1.3	0.0	1.3	1.4	2.6	0.0	26.3
1400-1500	Pro	2.3	46.5	23.3	1.3	0.4	19.9	4.2	1.3	0.0	0.9
	Ocp	1.1	1.5	2.1	2.4	8.5	1.6	1.1	6.4	0.0	18.5
1500-1600	Pro	1.9	46.4	26.9	1.9	0.4	14.3	4.4	2.1	0.0	1.6
	Ocp	1.2	1.5	2.1	4.0	7.5	1.4	1.3	5.5	0.0	10.3
1600-1700	Pro	1.0	55.1	19.9	0.8	0.4	16.0	2.1	2.5	0.0	2.1
	Ocp	1.2	1.6	2.2	5.3	14.0	1.3	1.4	1.5	0.0	9.1
1700-1800	Pro	3.3	55.8	23.3	0.6	0.2	10.6	1.5	2.7	0.0	2.0
	Ocp	1.1	1.4	1.9	5.7	20.0	1.4	1.1	2.9	0.0	8.1
1800-1900	Pro	3.1	62.8	22.6	0.0	0.5	6.8	0.5	1.7	0.0	2.0
	Ocp	1.1	1.4	1.9	0.0	20.0	1.3	1.3	4.8	0.0	8.0
1900-2000	Pro	3.2	64.0	23.5	0.2	0.4	3.9	2.6	0.2	0.0	1.9
	Ocp	1.1	1.4	1.8	1.0	11.0	1.3	1.2	14.0	0.0	7.8
2000-2100	Pro	4.1	54.1	28.8	0.0	0.0	6.1	2.0	1.7	0.0	3.2
	Ocp	1.2	1.4	1.6	0.0	0.0	1.7	1.2	2.0	0.0	6.2
2100-2200	Pro	2.5	50.7	36.8	0.7	0.0	3.9	1.8	0.7	0.0	2.9
	Ocp	1.0	1.4	1.5	1.0	0.0	1.3	1.2	10.0	0.0	5.3
2200-2300	Pro	4.0	46.0	36.3	0.0	0.0	5.7	3.6	1.2	0.0	3.1
	Ocp	1.1	1.3	1.7	0.0	0.0	1.1	1.3	6.7	0.0	5.1
16 hours	Pro	2.5	49.9	25.4	1.0	0.2	13.6	3.8	1.9	0.1	1.6
	Ocp	1.1	1.4	2.0	5.1	14.5	1.5	1.3	7.8	1.0	21.4

Legend: Pro. Proportion of vehicles in % (Sum may not add up to 100% due to figure rounding)*

Ocp. Average occupancy of vehicles including both driver and passengers*

M&H Medium and Heavy

* All traffic data are collected from combined bounds